

NEW


Root Grapples

& Grapple Buckets





HEAVY DUTY AND
DEMOLITION GRADES



ROOT GRAPPLE & GRAPPLE BUCKET BENEFITS:

- Move bulky hard-to-handle materials easily and securely.
- IDEAL FOR LOADING OR PILING LOGS AND BRUSH.
- **B**EST CHOICE FOR CLEAN-UP OF DEMOLITION AND STORM DEBRIS.
- ROOT GRAPPLES LET THE DIRT SIFT OUT WHEN LOADING LARGE ROCKS AND TRASH.
- ROOT GRAPPLE TINES CURVE UPWARD PREVENTS CATCHING UTILITY LINES OR CABLES IN STORM CLEAN-UP.

ROOT GRAPPLE & GRAPPLE BUCKET FEATURES:

- RUGGED HEAVY DUTY CONSTRUCTION FOR DEPENDABILITY AND LONG LIFE.
- HYDRAULIC CYLINDERS OPERATE INDEPENDENTLY TO ADJUST FOR UNEVEN LOADS.
- HYDRAULIC CYLINDERS, HOSES AND FITTINGS ARE PROTECTED WITH COVERS.
- GREASE ZERKS AT ALL PIVOT POINTS.
- CUTTING EDGES ARE PUNCHED FOR OPTIONAL BOLT-ON-BLADE.
- OPTIONAL INTERMEDIATE BOTTOM TINES REDUCES SPACE BETWEEN TINES.

THE PERFECT CHOICE FOR

- LAND CLEARING
- **DEMOLITION**
- CONSTRUCTION
- LANDSCAPING
- STORM CLEAN-UP



Heavy Duty

Demolition Grade

Model 170DG-72 Larger Capacity Demolition Grade Root Grapple

''
Cylinder Hoses routed in enclosed tube.
Built-in cover protects fittings.

	66" Root Grapple	72" Root Grapple	72" Root Grapple
Specifications:	Model 170-66	Model 170-72	Model 170DG-72
Width I.D.	66"	72"	72"
Grapple Capacity	15.8 cuft.	17.2 cuft.	19.7 cuft.
Grapple Opening	35½"	35½"	42¾"
Depth	38"	38"	42"
Back Height	21"	21"	21"
Sides	½" Plate	½" Plate	½" Plate
Grapple Thickness	1/2"	1/2"	9/16"
Tine Thickness	1/2"	1/2"	1/2"
Tine Height	3½"	3½"	5"
Distance between Tines	approx. 8½"	approx. 8½"	approx. 8½"
HD Welded Hyd Cylinders	2"x10"x11/4"	2"x10"x11/4"	2"x10"x11/4"
Hyd Hoses &	Included	Included	Included
Flat Faced Couplers	Included		
Empty Weight	725 lbs.	750 lbs.	950 lbs.

Heavy Duty

Note: Demolition Grade is especially recommended for "Track" style Skid-Steers and those with 70Hp or 3,500 lbs. capacity or greater.

Grapple Buckets

HEAVY DUTY AND DEMOLITION GRADES



Cutting edges are punched for optional Bolt-on-Blade.



Heavy Duty Grapple Bucket



Steel plate ribs 1/2" thick reinforce and protect bucket bottom.



Demolition Grade Grapple Buckets

Heavy Duty

Feature larger capacity, inside reinforcement gussets, and heavier components for greater durability in tough applications.

Heavy Duty

Included

800 lbs.

Demolition Grade


Included

1,000 lbs.



Optional End Plates help contain loose materials.

	66" Grapple Bucket	72" Grapple Bucket	72" Grapple Bucket
Specifications:	Model 175-66	Model 175-72	Model 175DG-72
Width I.D.	66"	72"	72"
Grapple Opening	38½"	38½"	45"
Grapple Capacity	16.5 cuft.	18 cuft.	24 cuft.
Bucket Capacity			
(w ith end plates)	11.6 cuft.	12.66 cuft.	16.6 cuft.
Depth	34"	34"	39"
Bucket Back Height	19"	19"	21"
Bucket Bottom	1/4" Plate	1/4" Plate	1/4" Plate
Bucket Back	3/16" Plate	3/16" Plate	3/16" Plate
Sides	½" Plate	½" Plate	½" Plate
Bottom Wear Protection	½" Ribs	½" Ribs	½" Ribs
Grapple Thickness	1/2"	1/2"	⁹ / ₁₆ "
Cutting Edge	¾" x 6"	3⁄4" x 6"	1" x 8"
HD Welded Hyd Cylinders	2"x10"x11/4"	2"x10"x11/4"	2"x10"x11/4"



Note: Demolition Grade is especially recommended for "Track" style Skid-Steers and those with 70Hp or 3,500 lbs. capacity or greater.

Included

775 lbs.



4101 Garland Dr., Fort Worth, TX 76117 Ph. 817-485-6073 Fax 817-428-6008 **USA & Canada Toll Free 800-541-1797** www.starindustries.com

Hyd Hoses &

Empty Weight

Flat Faced Couplers

Dealer: